



Chennai Paints – Acrylic Wall Putty

Chennai paints wall putty is acrylic water based putty used for filling up of minor surface irregularities up to 3-4mm thickness. It can also be used on Wall and wooden surfaces. It is for internal application only. It is very economical and one of the best putty of its kind which provides strong and durable foundation compared to other conventional putty bringing out the best performances from the finished paints both in looks and durability.

SAILENT FEATURES

- We do not recommend mixing of pigments/stainer in Chennai Paints wall putty.
- Quality of painted surface is directly proportional to quality of un-painted surface.
- Paint can be applied on Chennai Paints wall putty with or without primer However, use of Chennai Paints – Super prime (Water Base) primer shall give cost advantage in case of expensive paints.



Pack Size 20kg, 10kg, 5kg & 1kg

 Water Base



Area of application, Benefits & Methods

- This putty has a special acrylic binder that ensures it has strong grip on the surface, herby increasing the life of the paint film.
- Chennai paints acrylic water based putty is to be used only on interior surfaces.
- It has better alkali resistance thus making it more suitable for new walls. It can be applied on old walls as well.
- It enhances breath ability and lesser porosity compared to other conventional putty improving the performances of paint much better.
- Due to the putty's exceptional whiteness and smoothness, paint like emulsion when painted over it will look richer. It is quick drying which will ensure faster completion of work.
- Allow all new masonry surfaces to dry out completely.
- Remove all loose or defective paint or powdery residue by scraping. Treat any Area affected by lichens, algae and moss with proper surface treatment chemicals.
- Fill up all minor cracks and defects with putty after applying one coat of Chennai paints super prime wall primer (water base). Allow it to dry.
- then sand with emery paper to smoothen the surface. The powder from sanding has to be wiped out completely. Apply second coat of Chennai paints wall primer (water base) on the puttied surface. Always apply primer in thin coats.
- Apply the putty using trowel, putty knife and leveller. No need to add additional water, as it is ready to use.
- Always store the containers in upright position, with the lid tightly closed, in a cool dry place Ensure good ventilation at all times. Do not breathe vapour or spray. Avoid Inhalation of dust by wearing a suitable nose pad during sanding and surface preparation. Wear eye protection during application.


Allow all new masonry surfaces to dry out completely.

STEP 1	Remove all loose or defective paint or powdery residue by scraping	
STEP 2	Treat any Area affected by lichens, algae and moss with proper surface treatment chemicals.	
STEP 3	Fill up all minor cracks and defects with putty after applying one coat of Chennai paints super prime wall primer	
Allow it to Dry		
STEP 4	Then sand with emery paper to smoothen the surface. The powder from sanding has to be wiped out completely.	
STEP 5	Apply second coat of Chennai paints wall primer (water base) on the puttied surface	
STEP 6	Apply the putty using trowel, putty knife and leveler. No need to add additional water, as it is ready to use.	

Storage & Shelf life

Open the Container just before use only. Factory sealed containers/ Bags of this product is guaranteed to be of first quality for nine (9) months if stored off the ground in a dry area. High humidity will reduce the shelf life of product.

Coverage



1 COAT
38 - 44
sq.ft/kg*



2 COAT
24 - 35
sq.ft/kg*

*Actual coverage may vary from the quoted coverage due to factors such as method and conditions of application and surface roughness and porosity



Information on Health & Safety

- All Chennai Paints products contain no added Lead, Mercury, Arsenic or Chromium
- Store the container with the lid tightly closed in an upright position, in a cool, dry and well ventilated location away from source of ignition and fire.
- Keep out of reach of children and away from food, drink May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Avoid contact with skin for prolonged period. In case of any contact with eyes, wash immediately with plenty of water and seek medical attention.
- Use protective equipments like rubber or polythene gloves, safety goggles or glasses, face mask while handling the paint.
- Do not pour leftover paint down the drain or in water courses. In the event of spills, contain spillage using sand

Note- Specifications subject to change without notification. The technical data provided is as per our internal lab testing and may vary as per the actual installation method of application done at site

Disclaimer – Information provided on this data sheet is only a guideline for usage. It is advised to undertake a trial of the product before full scale usage. Any information and / or specification contained / shared herein is to the best of our knowledge true and accurate, no guaranty / warranty is given or implied in connection with any recommendation or suggestions made by us the company (Chennai Paints), our Representatives, Agents or Distributors, as the conditions of use of any labour involved, site conditions are beyond our control.

Product TDS No. AP -01/04/2024. Please note that this datasheet supersedes all previous versions. For Feedback/complaints, write to Marketing Manager Services, Chennai paints-200A, M.H.Road, Chennai-600-060. Tamilnadu India