



Chennai Paints – Surfaces+ Premium Interior Emulsion Paint

Chennai Paints –Surfaces+ Premium Emulsion provides a rich looking smooth and matt finish to the wall as its is Acrylic Based enhancing the beauty of the wall for years . due to its unique Stain resistant technology it delays stains from penetrating further into the paint film and can be wiped clean easily as its anti-bacterial property aids to inhibit growth of certain bacteria that protects your walls that can cause considerable damage . It has a Long lasting film that keeps your house as good as new for years.

Features & Benefits

- Enhances paint life
- Superior Hiding
- Stronger Adhesion for paint system
- Smoother Finish
- No Curing
- No chalking
- Good sealing properties
- Washability- High



Pack Sizes 18, 9, 3.6 & 0.900 liter containers. (Base paints)



Application and Direction for Use

PLASTER

New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.

CLEANING

Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water. When the underlying surface exhibits chalkiness, in spite of thorough surface cleaning, use a good quality Exterior Sealer.

FILLING FOR CRACKS, HOLES & DENTS

In case of Cracks, dents and holes use Chennai Paints Acrylic Wall Putty or white cement based and fine sand in the ratio 1:3.



Application

- Sanding – Rub with sand paper lightly scraping off previous coatings of loose dust, dirt particles making the surface smooth. (Sand the Surface With Sand Paper- 180 And Wipe Clean)
- Primer –Apply Chennai Paints Superprime Wall primer–Water based (Brush/Roller/Spray) Recoating to be done after 4 - 6 HRS
- Putty – Apply Chennai Paints Acrylic Wall Putty – Water based - Recoating to be done after 6 - 8 HRS
- Sanding Sand The Surface With Sand Paper 180 And Wipe Clean
- Primer – Apply Chennai Paints Superprime Wall Primer- Water based-(Brush /Roller /Spray) Recoating to be done after 4 - 6 HRS
- Sanding - Sand The Surface With Sand Paper 220 And Wipe Clean
- Apply 1st Coat of Surfaces+ Premium Emulsion – Water Based (Brush /Roller /Spray) Recoating to be done after 3 - 4 HRS
- Apply 2nd Coat of Surfaces+ Premium Emulsion- Water Based (Brush /Roller /Spray)

(Recoat period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.)



Direction for Use

Rub with sand paper lightly scraping off previous coatings of loose dust

STEP 1

Apply Chennai Paints Super prime Wall primer -Water based



STEP 2

Apply Chennai Paints Acrylic Wall Putty – Water based



STEP 4

Recoating to be done after 6 - 8 HRS



STEP 5

Sand The Surface With Sand Paper 180 And Wipe Clean



STEP 6

Apply Chennai Paints Super prime Wall Primer - Water based



STEP 7

Recoating to be done after 4 - 6 HRS



STEP 8

Sand The Surface With Sand Paper 220 And Wipe Clean



STEP 9

Apply 1st Coat of Surfaces+ Premium Emulsion - Water Based



STEP 10

Recoating to be done after 3 - 4 HRS




STEP 11

Apply 2nd Coat of Surfaces+ Premium Emulsion-Water Based



Coverage

*On normal masonry surface after brushing- 1 Coat covers 150 - 170 sq.ft/ltr and 2 coat covers 75 - 85 sq.ft/ltr



*Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity

Note

Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application. Do not over-thin or over-extend the brush. Always Tint using machine colorants only (Never use Universal Stainers) Stir well and strain before use. Tinted paints need thorough shaking immediately after tinter addition as well as before use.

TECHNICAL DETAILS

- **Nature** Free Flowing Liquid
- **Colour** Milky white (Base Paint)
- **Dilution Ratio** 10% by volume with clean and portable water
- **Sheen Level** Smooth & Matt.
- **Application** By Brush/Spray/ Roller.

- **Shelf Life** 16-18 Months from the date of manufacture in original company's tightly Sealed packing away from direct sunlight and excessive heat.



Information on Uses & Safety

- All Chennai Paints products contain no added Lead, Mercury, Arsenic or Chromium
- Store the container with the lid tightly closed in an upright position, in a cool, dry and well ventilated location away from source of ignition and fire.
- Keep out of reach of children and away from food, drink , harmful if swallowed. In case of ingestion seek immediate medical attention.
- Avoid contact with skin for prolonged period. In case of any contact with eyes, wash immediately with plenty of water and seek medical attention.
- Use protective equipments like rubber or polythene gloves, safety goggles or glasses, face mask while handling the paint.
- Do not pour leftover paint down the drain or in water courses. In the event of spills, contain spillage using sand
- Left-Over Paint Disposal: Left-over paint/drums should not be disposed in soil/drains.
- Consumers should consult a local recycling agency for proper disposal of paint/drums.

Note - Specifications subject to change without notification. The technical data provided is as per our internal lab testing and may vary as per the actual installation method of application done at site

Disclaimer – Information provided on this data sheet is only a guideline for usage. It is advised to undertake a trial of the product before full scale usage. Any information and / or specification contained / shared herein is to the best of our knowledge true and accurate, no guaranty / warranty is given or implied in connection with any recommendation or suggestions made by us the company (Chennai Paints), our Representatives, Agents or Distributors, as the conditions of use of any labour involved, site conditions are beyond our control.